



## CERTIFICATE OF COMPLIANCE BLANKET TYPE: SNG – SINGLE NET EXCELSIOR

### **Manufacturer:**

Greenfix America, LLC  
P.O. Box 1459  
Brawley, CA 92227

**Greenfix America, LLC certifies that the SNG Erosion Control Blanket contains the following properties and characteristics:**

### **BASIC USE-**

The 100% Poplar Excelsior fiber erosion control blanket is designed to provide temporary ground cover for erosion protection, mulching and revegetation applications to limit the potential for sediment release on 2:1 un-vegetated slopes with moderate rainfall intensities. Also utilized to protect seeding, enhance germination on cut and fill slopes and for mine / land fill reclamation. May be used on steeper slopes when used in conjunction with an approved slope interrupter device (SID) or as recommended by a qualified design consultant.

### **MATERIAL SOURCE-**

The SNG Single Net Excelsior erosion control blanket consists of 100% high quality Poplar Excelsior fiber that is naturally absent of all noxious weeds.

### **MATERIALS AND PROPERTIES-**

The blanket is machine produced using 100% high quality **Poplar Excelsior** fibers evenly distributed over the entire area of the blanket to an approximate thickness of 3/8". The **Excelsior** fibers are sewn into a medium weight photo degradable top net. Also available in white rapid degrading and Biodegradable jute fiber netting. The blankets are 8' x 95.6' (85 sq. yds.) at a minimum weight of .8 lbs. per square yard. The functional longevity is approximately 3 and 12 Months depending on soil conditions, climate, geography and choice of netting. The blankets are rolled and then packaged in a degradable recycled poly sleeve. The product is in compliance with the data published on the attached data sheet and specifications

### **INSTALLATION-**

The SNG Single Net Excelsior erosion control blanket should be installed only after proper soil preparation is completed. All Greenfix America blankets are designed for ease of installation. Please reference the installation guidelines.

### **MATERIAL CONTENT AND ROLL SPECIFICATIONS-**

- **Excelsior Fiber-** 100% high quality **Poplar Excelsior** at .8 lbs. per sq. yd. minimum. (.433 kg./sq. meter)
- **Netting-** Medium weight photo-degradable top net at 1.6 lbs./1000 sq.ft. (25.4mm x 50.8mm)  
(Also available in white rapid degrading and Biodegradable jute fiber netting)
- **Thread-** Polypropylene stranded filament, degradable
- **Stitching-** 3 inch centers (7.6 cm.)
- **Width-** 8.0 ft. (2.4 m)
- **Length-** 95.6 ft.(29.1 m)
- **Weight-** Minimum of 68 lbs. per roll (30.8 kg) +/- 10%
- **Area-** 85 sq. yds. (71 sq. meters)

### **WARRANTY**

Greenfix America, LLC warrants that its products are free from defects and will perform as stated in this literature. However, it is recommended that the product be stored in its package or under cover prior to installation. Greenfix America, LLC warrants the performance of their product from failure for a period of 60 days after purchase provided that the product was used in an application that was designed and specified by a qualified engineer. If our product does not meet products specifications, notice of failure must be received within 15 days of failure. Greenfix America, LLC will not warrant that the product will perform under unlimited circumstances that are caused by soil conditions, installation, and/or weather variables. Failure is defined as excessive soil loss as determined not to be caused by the variables mentioned above. To the best of our knowledge the information contained herein is accurate and final suitability of the product is the sole responsibility of the user.